

# GreensPro<sup>TM</sup> 1200 Riding Greens Roller

#### FEATURES

### Riding Greens Roller

- Offset, independent rollers for improved contour following and reduced striping.
- Wide turning radius helps minimise scuffing and turf damage
- Easy-to-operate foot pedals control the speed of side-to-side operation
- Converting from operating to transport mode can be done by one person without tools
- Easily adjustable seat does not affect the weight distribution of the machine, ensuring even rolling, regardless of the operator
- As with all Toro equipment, high quality Toro Genuine Parts available
- Warranty: Two-year limited manufacturer's warranty.

### Keeping Your Greens Smooth Just Got Easier!

The new Toro GreensPro 1200 riding greens roller is the perfect rolling tool for areas such as golf courses, bowling greens, tennis courts and other sporting fields. Any fine turf area that requires a smooth, high performance surface for optimum playing will benefit from precision rolling. Carefully engineered and manufactured, the GreensPro will provide safe, dependable and reliable service for years to come.



## GreensPro™1200 Specifications

GREENSPRO 1200	
ENGINE	Honda GX200 4.8 kW (6.5 hp) air-cooled, 4-stroke OHV; mechanically governed.
FUEL	Unleaded petrol
TRANSMISION	Hydrogear BDR-317
DRIVE	Twin chain to rear drive roller
SMOOTHING ROLLS	89 mm (3.5") diameter - 4 split rollers. Overlapping twin steering heads.
TRACTION DRIVE ROLLER	165 mm (6.5") diameter vulcanized rubber coated cylinder, 76 cm (30") long
ROLLING WIDTH	120 cm (47.2")
GROUND SPEED	Roll: 0-10 km/h (0-6 mph) in either direction
CONTROLS	Steering wheel, directional foot pedals
CONTOUR FOLLOW	Yes
COMPACTION	0.26 Bar (3.75 PSI)
STEERING	Wheel (light)
SEAT	High-back, adjustable
TRAILER	Integrated
LIFTING TYRES	16 x 6.50 - 8
LIFTING TYRE PRESSURE	0.69 Bar (10 PSI)
OVERALL DIMENSIONS	
WIDTH	122 cm (48")
LENGTH	136 cm (53.5")
HEIGHT	107 cm (42")
WEIGHT	240 kg (530 lbs.)
WARRANTY	Two-year limited warranty. Refer to operator's manual for further details.

