


400 Series Valves



Application:

These glass-reinforced globe valves offer superior performance and durability under demanding conditions. These valves are ideal for repeat and constant on/off cycling, which make them suitable for agricultural, greenhouse and nursery applications.

3/4" and 1" Plastic Valves

Features:

Performance

- Electric globe style valves available in 3/4" and 1" FPT
- Working pressure range 10 to 142 psi
- Flow rate 5 to 35 gpm
- Compact, ideal for small places
- Manual internal bleed
- Includes 24 VAC encapsulated solenoid, 0.4 amp inrush, 0.2 amp holding
- Flow control allows precise flow adjustment and manual shut-off
- Glass reinforced nylon body and bonnet
- Thermoplastic rubber diaphragm



400 Series Valves

Pressure Loss in PSI

Flow Rate (GPM)										
Model	Size	5	10	15	20	25	30	35	40	
40075	3/4"	6.4	6.0	3.4	4.5	7.3	10.9	_	_	Pressure L
400-1	1"	5.3	6.4	5.1	4.1	5.3	7.1	9.3	-	Loss PSI

Example: How To Order: 400 .75 <u>Solenoid</u> Model 400-.75 3/4" (19mm) 400-1 1" (25mm) Yes

Electrical Specifications

• Solenoid: 24 VAC

• Inrush volt-amp: 24 VAC-11.50 VA

• Inrush current: .4 amp

• Holding volt-amp: 24 VAC-5.75 VA

• Holding current: .2 amp

Replacement Diaphragm Kit:

<u>Model</u> <u>Size</u> VHP025-92 3/4" & 1"



ALT005 4/03

1588 N. Marshall Avenue, El Cajon, CA 92020-1523, USA Tel: +1 (800) 333-8125 or +1 (619) 562-2950 Fax: +1 (800) 892-1822 or +1 (619) 258-9973

www.toroag.com