

TORO

Count on it.

STX-38 Stump Grinder

THE TORO® STX-38 STUMP GRINDER is built for outstanding durability in the toughest conditions. Fully hydraulic operation means no chance of expensive belts breaking or slipping and no tension adjustments. The Intelli-Sweep feature automatically slows the sweep speed of the cutting head based on the load of the wheel, so heavy cutting loads won't bog down the engine. And with easy-to-use TX-style controls and tracks for maneuverability and stability, the STX-38 is extremely operator-friendly. Best of all, ground speeds of 4.5 mph allow you to spend more time grinding — and less time transporting the machine — for greater productivity.

FEATURES

HYDRAULICALLY DRIVEN HEAD

- Eliminates labor of tightening or replacing costly poly-chain® belts or clutches
- No need to replace expensive cogged pulleys
- No worry of customers engaging grinder head at full throttle
- Eliminates shock loads to the engine from belts slipping or head stopping
- Heavy-duty sealed, greaseable bearing housing and cutter shaft minimize maintenance.

- Intelli-Sweep feature automatically adjusts sweep speed based on the load on the wheel to maintain optimal operation

HI-DRIVE TRACK SYSTEM

- Low center of gravity and large footprint increase stability on side hills
- Eliminates tire ruts and flat tires
- Operates in soft, wet ground conditions
- Track design climbs curbs and allows for zero turn capability

USER-FRIENDLY DESIGN

- Single-cylinder sweep and lift design delivers a straight cut
- All-hydraulic sweep control valve facilitates side-to-side feathering
- Kohler® Command PRO® 980cc engine with electric start delivers reliable power
- 34" machine width — easily fits through 36" gates
- Frame design provides excellent cutter wheel visibility



STX-38
Stump Grinder

STX-38

Advanced Performance
& Easy Operation



STX CONTROL SYSTEM OPERATES WITH TWO EASY CONTROLS

Easy-to-use control system offers smooth operation and fewer levers/knobs than conventional stump grinders. An armrest near the joystick also reduces operator fatigue.

- 1 Steering System (forward, reverse, turn) allows for zero turn capability
- 2 Sweep, lift/lower and engagement of grinder head

SPECIFICATIONS

MODEL 23212	
Engine	Kohler® Command PRO® CV980 980cc 38 hp 4-cycle gasoline air-cooled engine
Hydraulics	Dual hydrostatic traction drive – 16 cc hydropumps with 15 gpm max flow to each side; 20 gpm gear pump flow to the piston motor driving the cutter head
Wheel	22.25" diameter to tooth; 1" thick; 16 Greenteeth cutting teeth
Cutter Depth	18" below grade
Cutter Height	35" above grade
Head Swing	52" radius x 60° sweep arc
Dimensions	34" (86 cm) W x 95" (241 cm) L (transport) x 51" (130 cm) H
Weight	1750 lb (794 Kg)
Max. Travel Speed	4.5 mph
Compliance	CE and EPA compliant

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties.

Worldwide Headquarters
The Toro Company
8111 Lyndale Ave. So.
Bloomington, MN 55420
Phone: 1-952-888-8801

toro.com

490-8628
©2013 The Toro Company
All Rights Reserved.



Count on it.