

TORO

Count on it.

TORO® PRO SNEAK™ 365 Vibratory Plow and Trencher



COMPACT AND POWERFUL



Introducing the redefined Pro Sneak™ 365 From Toro®.

The name may have changed, but the reputation remains the same. Toro's Pro Sneak™ 365 Vibratory Plow delivers powerful plowing in a compact, maneuverable package. It all adds up to reliable performance job after job.

Since 1914, the Toro Company has built its reputation on providing quality products and service to the professionals who create, maintain and preserve outdoor environments. Today, professionals and contractors around the world count on Toro products to stand up to the demands of heavy use, season after season.

As a leading manufacturer of turf maintenance equipment, precision irrigation solutions, concrete and compaction tools, and equipment for trenching and horizontal directional drilling, Toro products are aimed at allowing you to do your job more efficiently and profitably.

We value the trust professionals place in our people and products to meet their unique needs and deliver superior results. That's why the Toro Pro Sneak and every product that carries the Toro name also carries our commitment to quality and product excellence.



CONSISTENT PLOWING Optimized plow design provides down pressure to maintain consistent plowing up to 24" deep in a variety of conditions. The 10-degree frame oscillation ensures constant wheel-to-ground contact when plowing over rough terrain or crossing open trench lines.



INCREASED TRACTION AND STABILITY and mimizes impact on soft turf with optional dual wheel configuration. Dual wheels available in two sizes.



SAFE AND EASY OPERATION due to an optimized operator's position that allows operator to see all 4 tires while trenching, plowing or transporting. Adjustable seat ensures maximum operator comfort.

PRECISE CONTROL from low-effort, dual-lever ground drive controls for creep and transport modes.



EASY-TO-READ system gauges and indicator lights are grouped together for high visibility.

MAXIMUM MANEUVERABILITY as a result of hydraulic steering allowing articulation to a full 28-degrees to the left or right of center for a minimum inside turning radius of 72" (183 cm).



PRODUCTIVE TRENCHING with optional front-mounted, hydraulically-driven trencher. Dig depths of 24" or 36" (61 cm or 91 cm).

ADDED VERSATILITY from optional Hydra-Borer attachment. Hydra-Borer's high rotational torque provides smooth boring and back reaming through difficult soil conditions beneath driveways and walkways.



COMPACT FOOTPRINT 23" (58 cm) tires mounted narrow and inward allows easy access to tight spaces — less than any other riding vibratory plow. 26" (66 cm) or 23" (58 cm) tire options can be easily mounted inward for narrow width configuration or outward for added stability.

RELIABLE POWER Yanmar® 3TNV88C-DTR4 stroke, liquid cooled engine, provides gross 36.8 HP (27.5 kW) at 3,030 RPM to ensure constant performance while plowing or trenching.

PRO SNEAK 365 (MODEL 25403)

SPECIFICATIONS

DIMENSIONS

Width (with 23x10.5x12 tires) (Standard tire configuration)	46" (117 cm) mounted wide (standard); 36" (91 cm) mounted narrow
Width (with 26x12x12 tires)	46" (117 cm) mounted wide (standard); 40.5" (103 cm) mounted narrow
Wheelbase	48" (122 cm)
Overall Height (with ROPS and 23x10.5x12 tires)	85" (216 cm)
Overall Length (with plow and blade, no trencher)	114" (290 cm)
Ground Clearance (with 23x10.5x12 tires)	5.25" (13.3 cm)
Operating Weight (with 23x10.5x12 tires, ROPS and vibratory plow less blade)	2,930 lbs (1,329 kg)

POWER

Engine	Yanmar® 3TNV88C-DTR4 (Tier 4 Final)
Fuel Type	Diesel
Fuel Tank Capacity	7.1 gal (26.9 L)
Cooling	Liquid
Cylinders	3
Displacement	100.2 cubic inches (1.642 L)
Bore	3.46" (88 mm)
Stroke	3.54" (90 mm)
Net Power Rating per SAE J1349	36.8 hp (27.5 kW)
Rated Speed	3,030 rpm
Battery	12-Volt, 1000 cranking amps

PERFORMANCE

Ground Drive	Hydrostatic
Ground Drive Pump Flow Rate	27.7 gpm (105 L/m)
Attachment Pump Flow Rate	16.4 gpm (62 L/m)
Ground Drive Speed; Forward & Reverse (with 23x10.5x12 tires)	0 to 3.6 mph (0 to 5.8 km/h)

VIBRATORY PLOW

Maximum Plow Depth	24" (61 cm)
Vibrations	2,381 vpm
Angle of Approach	35°
Angle of Departure	35°

TRENCHER

Boom Options 36" (91 cm) Boom 24" (61 cm) Boom	36" (91 cm) trench depth 24" (61 cm) trench depth
Chain Options	Cup, combo or shark teeth; 6" (15 cm) width (4" spacers available through Toro parts)
Trencher Head Shaft to Wheelbase	38.5" (98 cm)
Boom Travel (up/down)	45°/60°

OPTIONAL EQUIPMENT

- Single Tires: 26x12x12
- Dual Tires: 23x10.5x12 or 26x12x12
- Hydra-borer System
- Wheel Weights
- Reel Carrier
- Trenchers
- Crumber
- Chains (Cup, combo or shark teeth)

