

Pro-Loc[™] **Fittings**



Easy to Spot. Tough to Beat.

Easy-to-install Pro-Loc drip tape fittings are available in a wide range of configurations, including a full line of valve options. Pro-Loc fittings are also available for hose and dripline — designed to last for the life of the irrigation system.

Features and Benefits

Pro-Loc fittings deliver the quality you expect from Toro for reliable performance, season after season.

Pro-Loc Fittings

- Tight Seal Coarse thread ensures a tight seal, even in dirty conditions.
- Easy to Install Easy-to-grip nut provides a secure connection every time.

Pro-Loc Drip Tape Fittings

- Easy to See Bright blue nut makes tape fittings easy to find, remove and reuse.
- Low Profile Compact design doesn't interfere with retrieving the tape.

Female Hose wivel Fittings Now Available for Hose



DRIP TAPE FITTINGS

PRO-LOC TAP	PE FITTINGS	
Couplings		
-	FTC500	5/8" Tape Coupling
	FTC700	7/8" Tape Coupling
Barb Adapter	s	
	FTA5-250B	5/8" Tape x 250 Series Barb Adapter
X	FTA5-400B	5/8" Tape x 400 Series Barb Adapter
S	FTA5-700B	5/8" Tape x 700 Series Barb Adapter
20	FTA7-700B	7/8" Tape x 700 Series Barb Adapter
The same	FTA5-425G	5/8" Tape x 425 Series Barb Adapter with Integral Gasket*
*	FTA5-425GR	5/8" Tape x 425 Series Barb Adapter with Rubber Grommet*
The second	FTA7-425GR	7/8" Tape x 425 Series Barb Adapter with Rubber Grommet*
Grommets		
	FTHG4	Top Hat Grommet for 400 - 425 Series Barbs
Adapters		
	FTA5-75FHS	5/8" Tape x 3/4" Female Hose Swivel Adapter
	FTA5-75MPT	5/8" Tape x 3/4" MPT Male Adapter
	FTA7-75MPT	7/8" Tape x 3/4" MPT Male Adapter
Flush Valves	T .	
	FFVFPT-L	Automatic Flush Valve x 3/4" Female Low Flow - White
	FFVFPT-H	Automatic Flush Valve x 3/4" Female High Flow - Red
	FTA5-FVL	5/8" Tape x Low Pressure Flush Valve
1	FTA7-FVL	7/8" Tape x Low Pressure Flush Valve
Layflat Takeo	ff Fittings	
CA	FTA5-LF	5/8" Tape x Layflat Takeoff - Single Grip**
-	FTA7-LF	7/8" Tape x Layflat Takeoff - Single Grip**
	FTA5-LF2	5/8" Tape x Layflat Takeoff - Double Grip**

PRO-LOC TAP	PE FITTINGS			
T-Handle Hex	Tool			
7	LF-INST	T-Handle Hex Tool for Layflat Installation		
Barbed Hose	Adapters			
	FTA5-500HB	5/8" Tape x 500 Series Hose Barb Adapter		
The same of the sa	FTA5-700HB	5/8" Tape x 700 Series Hose Barb Adapter		
	FTA7-700HB	7/8" Tape x 700 Series Hose Barb Adapter		
Tees				
	FTT500	5/8" Tape Tee		
17	FTT700	7/8" Tape Tee		
Barbed Tees				
	FTT5-500HB	5/8" Tape Tee x 500 Series Hose Barb		
17	FTT5-700HB	5/8" Tape Tee x 700 Series Hose Barb		
Shutoff Valve	s			
-	FTV500	5/8" Tape Shutoff Valve		
	FTV700	7/8" Tape Shutoff Valve		
-	FTV5-250B	5/8" Tape x 250 Barb Adapter Shutoff Valve		
The state of the s	FTV7-250B	7/8" Tape x 250 Barb Adapter Shutoff Valve		
	FTV5-400B	5/8" Tape x 400 Barb Adapter Shutoff Valve		
The state of the s	FTV7-400B	7/8" Tape x 400 Barb Adapter Shutoff Valve		
Barbed Shuto	off Valve with Lo	ocking Nut		
	FTV5-420BN	5/8" Tape x 420 Series Barb with Locking Nut Shutoff Valve		
The same of the sa	FTV5-500HN	5/8" Tape x 500 Series Hose Barb with Locking Nut Shutoff Valve		
Barbed Shutoff Valves				
1	FTV5-500HB	5/8" Tape x 500 Series Hose Barb Shutoff Valve		
	FTV7-500HB	7/8" Tape x 500 Series Hose Barb Shutoff Valve		
Layflat Takeo	ff Shutoff Valve			
	FTV5-LF	5/8" Tape x Layflat Takeoff Shutoff Valve**		
and de	FTV7-LF	7/8" Tape x Layflat Takeoff Shutoff Valve**		

- * 15mm or 0.59" drill size
- ** Requires a 14mm layflat punch

HOSE AND DRIPLINE FITTINGS

PRO-LOC HOSE AND DRIPLINE FITTINGS				
Couplings				
	FHC500	500 Series Pro-Loc Coupling		
	FHC600	600 Series Pro-Loc Coupling		
300	FHC700	700 Series Pro-Loc Coupling		
}	FHC800	800 Series Pro-Loc Coupling		
Threaded Ada	apters			
	FHA5-50MPT	500 Series Pro-Loc x 1/2" Male Pipe Thread Adapter		
	FHA6-50MPT	600 Series Pro-Loc x 1/2" Male Pipe Thread Adapter		
~	FHA7-50MPT	700 Series Pro-Loc x 1/2" Male Pipe Thread Adapter		
The state of the s	FHA5-75MPT	500 Series Pro-Loc x 3/4" Male Pipe Thread Adapter		
	FHA6-75MPT	600 Series Pro-Loc x 3/4" Male Pipe Thread Adapter		
	FHA7-75MPT	700 Series Pro-Loc x 3/4" Male Pipe Thread Adapter		
	FHA8-75MPT	800 Series Pro-Loc x 3/4" Male Pipe Thread Adapter		
Threaded Adapters x 3/4" Female Hose Swivel				
	FHA5-75FHS	500 Ser Pro-Loc x 3/4" Female Hose Swivel		
	FHA6-75FHS	600 Ser Pro-Loc x 3/4" Female Hose Swivel		
	FHA7-75FHS	700 Ser Pro-Loc x 3/4" Female Hose Swivel		
	FHA8-75FHS	800 Ser Pro-Loc x 3/4" Female Hose Swivel		
	FHA5-75FHSS	500 Ser Pro-Loc x 3/4" Female Hose Swivel with Screen		
	FHA6-75FHSS	600 Ser Pro-Loc x 3/4" Female Hose Swivel with Screen		
	FHA7-75FHSS	700 Ser Pro-Loc x 3/4" Female Hose Swivel with Screen		
	FHA8-75FHSS	800 Ser Pro-Loc x 3/4" Female Hose Swivel with Screen		

PRO-LOC HO	PRO-LOC HOSE AND DRIPLINE FITTINGS			
Barbed Adapt	ters with Rubber	Grommet		
	FHA5-425RG	500 Series Pro-Loc x 425 Series Barb with Rubber Grommet*		
	FHA6-425RG	600 Series Pro-Loc x 425 Series Barb with Rubber Grommet*		
Side Co	FHA7-425RG	700 Series Pro-Loc x 425 Series Barb with Rubber Grommet*		
	FHA8-425RG	800 Series Pro-Loc x 425 Series Barb with Rubber Grommet*		
Layflat Takeo	ffs			
	FHA5-LF	500 Series Pro-Loc x Layflat Takeoff Single Grip**		
	FHA6-LF	600 Series Pro-Loc x Layflat Takeoff Single Grip**		
TOA	FHA7-LF	700 Series Pro-Loc x Layflat Takeoff Single Grip**		
40	FHA8-LF	800 Series Pro-Loc x Layflat Takeoff Single Grip**		
	FHA5-LF2	500 Series Pro-Loc x Layflat Takeoff Double Grip**		
T-Handle Hex	T-Handle Hex Tool			
7	LF-INST	T-Handle Hex Tool for Layflat Installation		

- * 15mm or 0.59" drill size
- ** Requires a 14mm layflat punch

PRO-LOC FITTINGS SELECTION GUIDE

Nominal	Series	Inside Diameter Tolerance		Wall Thickness Tolerance	
Size	Number	Inches	Millimeters	Inches	Millimeters
16mm & 17mm	500	0.519 - 0.590	13.2 - 15.0	0.020 - 0.055	0.50 - 1.40
18mm	600	0.598 - 0.649	15.2 - 16.5	0.030 - 0.055	0.75 - 1.40
20mm	700	0.677 - 0.728	17.2 - 18.5	0.032 - 0.055	0.80 - 1.40
22mm	800	0.787 - 0.846	20.0 - 21.5	0.040 - 0.059	1.00 - 1.50

HOSE AND DRIPLINE FITTINGS

PRO-LOC HOSE AND DRIPLINE FITTINGS			
Elbows			
_	FHE500	500 Series Pro-Loc Elbow	
	FHE600	600 Series Pro-Loc Elbow	
	FHE700	700 Series Pro-Loc Elbow	
6	FHE800	800 Series Pro-Loc Elbow	
Tees			
	FHT500	500 Series Pro-Loc Tee	
	FHT600	600 Series Pro-Loc Tee	
- W	FHT700	700 Series Pro-Loc Tee	
	FHT800	800 Series Pro-Loc Tee	
Tee x 3/4" Ma	ale Pipe Thread		
	FHT5-75MPT	500 Series Pro-Loc Tee x 3/4" Male Pipe Thread	
	FHT6-75MPT	600 Series Pro-Loc Tee x 3/4" Male Pipe Thread	
	FHT7-75MPT	700 Series Pro-Loc Tee x 3/4" Male Pipe Thread	
	FHT8-75MPT	800 Series Pro-Loc Tee x 3/4" Male Pipe Thread	
Tees x 3/4" Fe	emale Hose Swive	el	
	FHT5-75FHS	500 Ser Pro-Loc Tee x 3/4" Female Hose Swivel	
	FHT6-75FHS	600 Ser Pro-Loc Tee x 3/4" Female Hose Swivel	
	FHT7-75FHS	700 Ser Pro-Loc Tee x 3/4" Female Hose Swivel	
	FHT8-75FHS	800 Ser Pro-Loc Tee x 3/4" Female Hose Swivel	
	FHT5-75FHSS	500 Ser Pro-Loc Tee x 3/4" Female Hose Swivel with Screen	
	FHT6-75FHSS	600 Ser Pro-Loc Tee x 3/4" Female Hose Swivel with Screen	
	FHT7-75FHSS	700 Ser Pro-Loc Tee x 3/4" Female Hose Swivel with Screen	
	FHT8-75FHSS	800 Ser Pro-Loc Tee x 3/4" Female Hose Swivel with Screen	

PRO-LOC HOSE AND DRIPLINE FITTINGS					
Shutoff Valve	Shutoff Valves				
	FHV500	500 Series Pro-Loc Shutoff Valve			
	FHV600	600 Series Pro-Loc Shutoff Valve			
-	FHV700	700 Series Pro-Loc Shutoff Valve			
	FHV6-425G	600 Series Pro-Loc x 425 Series Barb Shutoff Valve with Grommet			
Male Thread	Shutoff Valves				
	FHV5-50MPT	500 Series Pro-Loc x 1/2" Male Pipe Thread Shutoff Valve			
	FHV6-50MPT	600 Series Pro-Loc x 1/2" Male Pipe Thread Shutoff Valve			
	FHV7-50MPT	700 Series Pro-Loc x 1/2" Male Pipe Thread Shutoff Valve			
	FHV5-75MPT	500 Series Pro-Loc x 3/4" Male Pipe Thread Shutoff Valve			
	FHV6-75MPT	600 Series Pro-Loc x 3/4" Male Pipe Thread Shutoff Valve			
	FHV7-75MPT	700 Series Pro-Loc x 3/4" Male Pipe Thread Shutoff Valve			
	FHV75MHT- 75FHS	3/4" Male Hose Thread x 3/4" Female Hose Swivel with Shutoff Valve			

^{* 15}mm or 0.59" drill size

PRO-LOC FITTINGS SELECTION GUIDE

Nominal	Series	Inside Diameter Tolerance		Wall Thickness Tolerance	
Size	Number	Inches	Millimeters	Inches	Millimeters
16mm & 17mm	500	0.519 - 0.590	13.2 - 15.0	0.020 - 0.055	0.50 - 1.40
18mm	600	0.598 - 0.649	15.2 - 16.5	0.030 - 0.055	0.75 - 1.40
20mm	700	0.677 - 0.728	17.2 - 18.5	0.032 - 0.055	0.80 - 1.40
22mm	800	0.787 - 0.846	20.0 - 21.5	0.040 - 0.059	1.00 - 1.50

HOSE AND DRIPLINE FITTINGS

BARBED HOS	BARBED HOSE FITTINGS AND DRIPLINE FITTINGS				
Barbed Coup	lings				
	FBC500	500 Series Barb Coupling			
0-	FBC700	700 Series Barb Coupling			
	FBC1000	1000 Series Barb Coupling			
0	FBC1200	1200 Series Barb Coupling			
	FBC1400	1400 Series Barb Coupling			
Barbed Tees	Barbed Tees				
	FBT500	500 Series Barb Tee			
	FBT700	700 Series Barb Tee			
	FBT1000	1000 Series Barb Tee			
	FBT1200	1200 Series Barb Tee			
	FBT1400	1400 Series Barb Tee			

BARBED HOSE FITTINGS AND DRIPLINE FITTINGS				
Male Thread	Adapters			
	FBA5-50MPT	500 Series Barb x 1/2" Male Pipe Thread Adapter		
	FBA7-50MPT	700 Series Barb x 1/2" Male Pipe Thread Adapter		
CCA	FBA10-50MPT	1000 Series Barb x 1/2" Male Pipe Thread Adapter		
	FBA5-75MPT	500 Series Barb x 3/4" Male Pipe Thread Adapter		
	FBA7-75MPT	700 Series Barb x 3/4" Male Pipe Thread Adapter		
	FBA10-75MPT	1000 Series Barb x 3/4" Male Pipe Thread Adapter		

BARBED FITTINGS SELECTION CHART

Nominal	Series	Inside Diameter		
Size	Number	Inches	Millimeters	
16mm & 17mm	500	0.519	13.2	
20mm	700	0.661	16.8	
25mm	1000	0.850	21.6	
32mm	1200	1.110	28.2	
40mm	1400	1.385	35.2	

Toro Micro-Irrigation Products



Toro Irrigation Solutions

PRECISE. EFFICIENT. PRACTICAL.

©2012 The Toro Company Micro-Irrigation Business 1588 N. Marshall Avenue, El Cajon, CA 82020-1523, USA Tel: +1 (800) 333-8125 or +1 (619) 562-2950 Fax: +1 (800) 892-1822 or +1 (619) 258-9973

toro.com

TORO. Cour