

TORO.

Count on it.

DL2000[®] Series Microline with ROOTGUARD[®]

Landscape Drip

As leaders in micro-irrigation innovations, Toro[®] has continued to provide solutions for many kinds of watering needs. Microline is a 1/4" dripline product with patented ROOTGUARD[®] protection. With the slow release of non-toxic Treflan[®] from the emitter opening, the ROOTGUARD process creates a "force field" effect guarding against root intrusion. The 1/4" size makes it easy to install and ideal for small tight areas such as planter boxes, flower beds or under narrow strips of turf. Just like other Toro dripline products, Microline is sturdy, flexible and requires minimal maintenance.

Features & Benefits

ROOTGUARD[®] Protection

Uses the non-toxic Treflan[®] creating a force-field effect guarding against root intrusion into the emitters.

1/4" Tubing With Built-in Emitters

Allows for ease of installation even to the smallest of areas.





DL2000® Series Microline with ROOTGUARD®



T-FCC0400



T-FTT0400



T-FEE0400



T-FCV-BB



T-FMP08



T-IPS0104

Length of Run Chart

| Part Number | Tubing Size | Flow Rate | Emitter Spacing | Inlet Pressure | Maximum Length of Run |
|-------------|-------------|-----------|-----------------|----------------|-----------------------|
| T-MCRG-206 | 1/4" | .53 GPH | 6" | 15 psi | 19' |
| T-MCRG-212 | 1/4" | .53 GPH | 12" | 15 psi | 33' |

Specifying Information Microline

| Part Number | Description |
|-------------|--|
| T-MCRG-206 | DL2000 100' Roll, 1/4" Non-pressure-compensating Microline Dripline w/ROOTGUARD, 6" Emitter Spacing, 0.50 GPH |
| T-MCRG-212 | DL2000 100' Roll, 1/4" Non-pressure-compensating Microline Dripline w/ROOTGUARD, 12" Emitter Spacing, 0.50 GPH |

Specifying Information— Microline 1/4" Fittings

| Part Number | Description |
|-------------|--|
| T-FTT0400 | Tee (Barb x Barb) |
| T-FEE0400 | Elbow (Barb x Barb) |
| T-FCC0400 | Coupling (Barb x Barb) |
| T-FCV-BB | Microflow Valve (Barb x Barb) |
| T-FMP08 | Hose Punch for 1/4" barbed fittings and emitter |
| T-IPS0104 | 1/4" (4mm) plastic locator stake to hold tubing in place |

Performance Table

| | |
|--------------------------------|-----------|
| Inside Diameter | 0.170" |
| Outside Diameter | 0.250" |
| Wall | 0.040" |
| Operating Pressure | 15–60 psi |
| Minimum Filtration Requirement | 140 Mesh |
| Nominal Flow Rate (Q) | 0.53 GPH |



www.toro.com • The Toro Company • Irrigation Division
5825 Jasmine St. • Riverside, CA • 92504 • 877-345-8676

Specifications subject to change without notice. For more information, contact your local Toro distributor. ©2010 The Toro Company. All rights reserved.
P/N 10-1062-IRC