

TORO Count on it.

Multi Pro[®] 1200 & 1250



TORO. Count on it.

Applied precision.

1200 & 1250:

- Triangular truss booms
- Toro Spray Pro™ System
- 663 litre (175 gallon) tank
- Dual-diaphragm pump

1200

- Manual spray control system

1250:

- Electronic spray control system

When working with turf chemicals, there is often a delicate balance between applying too much and not enough. Add varying turf conditions and precision can be hard to attain. The Toro® Multi Pro® 1200 and 1250 provide the simple calibration, precise control and ease of use required for the most demanding turfs.



Count on Durability

Toro builds a better boom.

Trees, benches and other obstacles are no match for the rugged new boom design on the Multi Pro. A triangular frame protects the spray nozzles from direct impact. Combined with the breakaway boom design, it's the ultimate defense against unexpected impact.





One sprayer does it all.

The key to a better sprayer is simplifying the application process. And nothing does that better than the Toro® Spray Pro™ System. This proportional drive spray system adjusts instantly to changes in ground speed to ensure a constant application rate. Slow down or speed up and the flow rate adjusts proportionally to ensure your application rate remains constant regardless of the terrain. Operators will appreciate the worry-free, consistent control along with the ergonomic cockpit, fingertip controls and foot-controlled master on/off switch. The rugged design of the Multi Pro® also features four-wheel brakes, a three-speed CVT automatic transmission and a dependable Kohler® 14.9 kW (20 hp) engine.



A 663 litre (175 gallon) tank lets you work longer between fills.

The Multi Pro is designed to accommodate a variety of nozzle sizes for precise application at any speed.





Refined durability.

Once you purchase a Multi Pro, you can rest assured, knowing it is built to last. O-ring fittings and a reliable, dual-diaphragm pump provide continuous leak-free performance for years of dependable service. Operator comfort and control is also a top priority. This led to the inclusion of a smooth-riding, front torsion joint suspension, a comfortable high-back seat and power steering.

The new open booms featured on Toro's sprayers add durability and allow for a more stable spraying platform to ensure a consistent application of chemicals on the turf.

The strong yet lightweight, triangular truss design provides protection to nozzles and allows for easy cleaning. In addition, the breakaway design allows the booms to return to application position if impacted with obstacles while spraying.

Attachments

- Standard boom
- Foam marking kit
- Electric hose reel kit
- Sonic boom
- Rinse kit
- Boomless nozzle
- Single nozzle kit
- Spray gun kit
- ROPS

Also available: Operator enclosure, sprayer protection system.



Make it your own.

A wide variety of accessories let you customize the Multi Pro to your specific needs. Other productive

options such as a foam marking kit and spray gun kit make spraying easier and more precise.

Specifications for Multi Pro® 1200 & 1250

Engine

Model: Kohler® V-Twin
Rating: 14.9 kW (20 hp), governed to 3350 rpm
Alternator: 30 amp
Battery: 12 volt, with 540 cold cranking amps @ -18°C (0°F).
Transmission: Integrated transaxle with 3 forward speed ranges and reverse

Traction Unit

Fuel capacity: 23 litre (6 gallon)
Brakes: 4-wheel hydraulic drum type with dual chamber master cylinder
Clutch: Centrifugally engaged variable belt drive (CVT)
Suspension: Front: fully independent rubber torsion swing arm; rear: rigid

Tyres

Front: 18 x 9.5-8 slick
Rear: 24 x 13-12, Multi-Trac

Ground Speed/Clearance

1st speed: 0-5 km/h (0-3 mph)
2nd speed: 0-8 km/h (0-5 mph)
3rd speed: 0-18 km/h (0-11 mph)
Ground clearance: 11.4 cm (4.5")

Controls

Steering: hydraulic power, center pivot linkage, 60° steering angle, 2.4 m (96") inside turning radius, 2.3 m (7'7") rear tire radius.
Lights: Twin halogen headlights

Weight

Empty vehicle: 1025 kg (2,261 lbs.)
Full w/operator: 1,751 kg (3,861 lbs.)
MGVW: 1,888 kg (4,136 lbs.)

Dimensions

Measurements with spray system
Wheelbase: 147 cm (58")
Length: 337 cm (133")
Width: 175 cm (69")
Height: 238 cm (94")

Sprayer System

Solution tank: Polyethylene, inductive agitation, low profile imbedded 75 litre (20 gallon) rinse tank and 18 litre (5 gallon) fresh water tank, translucent with fill level gauge
Capacity: 663 litre (175 gallon)
Spray pump: Dual diaphragm pump, proportional ground speed control system, 81 litre/min (21.5 gpm) output, capacity range up to 15 bar (220 psi) max.
Controls: Electronic switches on Multi Pro 1250, manual levers and dial on Multi Pro 1200.
Monitor: Spray Pro™ fully functional with liquid crystal display. Back lit for late evening/early morning operation.
Options: Pro Foam marking system, electric hose reel, spray gun kit, ROPS, rinse tank kit, single nozzle kit.

Open Boom (Standard)

Boom assembly: 3-section triangular truss open boom. Bi-directional breaks away. Raise criss-cross for storage and transportation. 5.6 m (18.5') working width.
Spray nozzles: Colour-coded, stainless steel, quick disconnect with diaphragm check valves, drift reduction mounted on triple nozzle bodies
Boom options: enclosed boom and Sonic Boom™ for added lift.

Certification: SAE J2258 and machinery directive 98/37 EC.

Warranty: Two year limited warranty. See operations manual for details.

TORO® PROFESSIONAL SERVICES

Toro Financing Many flexible financing options are available to meet your specific operational requirements.

Toro Genuine Parts Keep the productivity and performance of your equipment at its peak by using genuine Toro replacement parts. Find and identify your replacement parts online at www.Toro.com/partsviewer.

Toro Training Toro Technical Service Schools are available from your local distributor. Explore the training and customer care areas of Toro.com and ToroNSN.com for readily available on-line education and training materials.

Toro Controller Repair Provides irrigation controller boards ready for immediate board exchange to assure that downtime is minimal and your turf stays protected. Toro is the choice for reliability.

Toro NSN® An industry-first support network that provides reliable, around-the-clock irrigation central control system trouble-shooting and operation assistance. For assistance please contact:

Canada / Mexico / Latin America +1 325 673 8762

Europe / Middle East / Africa +32 14 56 29 33

Australia / Asia-Pacific +61 7 3268 2154

Products depicted in this brochure are for demonstration purposes only. Actual products offered for sale may vary.
©2007 The Toro Company, 8111 Lyndale Ave. S.,
Bloomington, MN 55420-1196
GB Part No. 200-3390. Printed in U.S.A.
www.toro.com



Count on it.