



# LT3340 Heavy Duty Triple Specifications\*

LT3340, Model 30657													
ENGINE	Kubota V1505 Liquid cooled, 4 Cylinder 26.5 kW (35.5 HP) @ 3000 rpm. 1.498 litres displacement												
AIR CLEANER	2 Stage. Replaceable primary and safety elements.												
RADIATOR	Rear mounted radiator. 3 Pass. Clean Core.												
FUEL CAPACITY	45 litres (10 imp gallons)												
HYDRAULICS	32 Litre (7.04 imp Gallon) Capacity with 10 Micron spin on filter, 125 micron suction strainer, 5 row, 8 fins per inch single pass oil cooler.												
TRACTION DRIVE	Parallel / Series hydraulic closed loop transmission circuit, provides 4-wheel drive on-demand, both forward and reverse. Hydrostatic traction drive, provides infinitely variable speed in forward and reverse.												
GROUND SPEED	0-25 km/h (0-15.5mph) Forward Speed, 0-11km/h (0-7mph) Reverse Speed												
BRAKES	Hydrostatic service braking. Parking brake on front wheels only.												
TYRES	Front 26 x 12 - 12. Rear 20 x 10 - 8 6 Ply												
CHASSIS	Formed and welded steel chassis with integral tie down eye at the front												
CONTROLS	Forward and reverse control pedals. Electrically operated parking brake. Ignition key switch. Pedal operated tilting steering column. Engine throttle control. Electric switch control for independent cutter lift / lower. Cutter on - off - reverse switch. Limited lift on reverse on / off switch. Horn switch. Differential lock switch												
OPERATOR AREA	Radio / mobile phone holder. Large storage pod (for waterproofs etc.). Drink holder.												
SEAT	Deluxe two cushion seat with arm rests, and retractable seat belt. Fore / aft adjustment, operator weight adjustment, seat back angle adjustment.												
STEERING	Hydraulic powered steering. Tilt steering column. Moulded steering wheel.												
GAUGES	Fuel Level Gauge. Hour Meter. Hydraulic Oil Level. Indicator lights for glow plug, charge and transmission neutral. Warning lights for engine oil pressure, hydraulic oil and engine coolant temperature.												
ELECTRICAL	12 Volt Battery. 40 amp alternator. Solid state logical controller.												
INTERLOCKS	Prevents engine from starting unless traction pedal is in neutral, cutter engage switch is not set to off, parking brake is on and operator is seated .Cutter control will switch off if operator is not seated while parking brake is off.												
ROPS													
MAXIMUM OPERATING SLOPE ANGLE	20 degrees without cab 16 degrees with cab. Measured to BS EN836 1997 Lawnmower safety requirements												
OVERALL DIMENSIONS	<table border="0"> <tr> <td>Overall Height ROPS Up</td> <td>2350mm (92.5")</td> </tr> <tr> <td>Overall Height ROPS Down</td> <td>1625mm (64")</td> </tr> <tr> <td>Wheel Base</td> <td>1525mm (60")</td> </tr> <tr> <td>Transport Width</td> <td>1575mm (62")</td> </tr> <tr> <td>Overall Length</td> <td>2860mm (112.6")</td> </tr> <tr> <td>Width of Cut</td> <td>2120mm (83.5")</td> </tr> </table>	Overall Height ROPS Up	2350mm (92.5")	Overall Height ROPS Down	1625mm (64")	Wheel Base	1525mm (60")	Transport Width	1575mm (62")	Overall Length	2860mm (112.6")	Width of Cut	2120mm (83.5")
Overall Height ROPS Up	2350mm (92.5")												
Overall Height ROPS Down	1625mm (64")												
Wheel Base	1525mm (60")												
Transport Width	1575mm (62")												
Overall Length	2860mm (112.6")												
Width of Cut	2120mm (83.5")												
WEIGHT	1290kg (2838 lbs) with full fluids, & 250mm 6 blade cutterheads.												
CERTIFICATION	CE certified												
WARRANTY	2-year limited warranty. Refer to the Operator's Manual for further details.												





# LT3340 Heavy Duty Triple Specifications\* (continued)

LT3340 CUTTING UNITS	
TYPE	Three hydraulically driven 200mm (8") or 250mm (10") diameter reels. Cutting units are interchangeable to all three positions
REEL BLADE OPTIONS	200mm - 4,6,8 & 10 blade reels & 250mm - 4, 6,& 8 blade reels.
HEIGHT OF CUT	12mm to 80mm (1/2" to 3")
CUTTING WIDTH	762mm (30")
BACKLAPPING	Standard on board backlapping.
BEDKNIFE TO REEL ADJUSTMENT	Two point adjustment of reel to bedknife.
ROLLERS	Full smooth roller as standard on rear of cutting unit. Optional smooth or grooved roller on front (when fitted with floating head kit option).
BLADES	Three, .25" (.6 cm) thick, 2.5" (6.3 cm) wide, heat-treated steel blades.

LT3340 OPTIONS	
KIT - ROAD LIGHTS W/ BRAKE LIGHTS	Model 02916
KIT - FLASHING BEACON	Model 02901
FULL WEATHER CAB WITH HEATER BLOWER, CAB TILT AND NOISE REDUCTION KIT	Model 02890
AIR CONDITIONING KIT	Model 02891
AIR CONDITIONER FITTING KIT - KUBOTA V1505 ENGINE	Model 02892
BLOWER / TOOL CARRIER KIT	Model 02903
ROPS ASSIST KIT	Model 02905
WASTE BIN KIT	Model 02906
TOOLBOX KIT	Model 02907
STD SEAT FABRIC UPGRADE KIT	Model 02864
DELUXE PVC SEAT KIT	Model 02865
DELUXE FABRIC SEAT KIT	Model 02866
LT KEVLAR TYRES KIT	Model 02914
MK3 200MM (8") 4-BLADE CUTTERHEAD	Model 02800
MK3 200MM (8") 6-BLADE CUTTERHEAD	Model 02801
MK3 200MM (8") 8-BLADE CUTTERHEAD	Model 02802
MK3 200MM (8") 10-BLADE CUTTERHEAD	Model 02803
FLOATING CUTTING UNIT KIT 3 - PLEX MOWER	Model 02820
SMOOTH ROLLER KIT (FOR FLOATING CUTTER UNIT KIT)	Model 02822
GROOVED ROLLER KIT (FOR FLOATING CUTTER UNIT KIT)	Model 02823
MK3 250MM (10") 4-BLADE CUTTERHEAD	Model 02810
MK3 250MM (10") 6-BLADE CUTTERHEAD	Model 02811
MK3 250MM (10") 8-BLADE CUTTERHEAD	Model 02812
TUV KIT - SPEED DECAL 20KPH	Model 02980
TUV KIT - DECK COVER 3-GANG	Model 02982
TUV KIT - GERMAN VEHICLE SERIAL PLATE	Model 02983

