



ProCore® Processor Specifications*

PROCORE PROCESSOR, MODEL 09749	
ENGINE	Briggs® Vanguard® 2 cylinder air-cooled 35 HP Gross, 31 HP Net, 993 cc displacement. High filtration replaceable element air filter. External spin on oil filter.
FUEL CAPACITY	10 gallons
PROCESSING WIDTH	70 inches
PROCESSING SYSTEM	Belt driven nylon brush sweeps material into chopper assembly equipped with carbide tips.
OPERATING SPEED	0-5 MPH
ROLLER	6" (15.2 cm) diameter full width rear roller.
CONSTRUCTION	Welded steel frame
HITCH SYSTEMS	Exclusive OnePass hitch allows attachment directly behind 3-point aerator. Offset tow hitch allows attachment to heavy duty work vehicle or tractor.
CONTROLS	Engine mounted key switch, choke and throttle. Remote mounted kill switch and offset control.
TRANSPORT TIRES	6-ply, 18 x 9.5 - 8
OVERALL WIDTH	88 inches
HEIGHT	44 inches
LENGTH	133 inches with OnePass hitch (09753), 170 inches with Tow Hitch (09750)
WEIGHT	2200 lbs
OPTIONS	Rear Wheel Kit (09768), Windrow Kit (09760), SMV (Slow Moving Vehicle) Kit
CERTIFICATION	ANSI B71.4-2004, OSHA, CE and EU machinery directives
WARRANTY	Two-year or 500-hour limited warranty. Refer to Operator's Manual for further details

*Specifications and design subject to change without notice.

