

# Workman® MD/MDX Specifications



	Workman MD	Workman MDX	
<b>Engine</b> .....	12 hp (9 kW), 357 cc, air-cooled, single-cylinder, Kohler® Command Pro™	14 hp (11.9 kW), 480 cc, air-cooled, 2-cylinder, Briggs and Stratton® Vanguard®	
<b>S.R.Q. System</b> .....	Active In-Frame™ twister pivot joint, front and rear suspension.		
<b>Front Suspension</b> .....	Independent "A"-Frame with coil over shock absorbers.		
<b>Rear Suspension</b> .....	Trailing arm with coil over shock absorbers.		
<b>Maximum Speed</b> .....	15-16 mph (24.1-25.6 km/h) governed.	16 mph (25.6 km/h) governed.	
<b>Brakes</b> .....	Front wheel hydraulic disc. Rear wheel hydraulic drum.		
<b>Frame</b> .....	Welded steel channel and tube in body construction. Frame surfaces are dipped in e-coat. Body and bed constructed of dent and corrosion resistant polyethylene.		
<b>Ground Clearance</b> .....	Front: 10" (25.4 cm), Rear: 7" (18 cm)		
<b>Tires</b> .....	Front: 22 x 9.5-10, 4-ply, Rear: 22 x 9.5-10, 4-ply	Front: 22 x 9.5-10, 4-ply, Rear: 24 x 12-10, 4-ply.	
<b>Fuel Capacity</b> .....	7 gallons (26.5 liters)		
<b>Dimensions</b> .....	<b>Width</b> 59" (150 cm)	<b>Length</b> 117.75" (299 cm)	<b>Wheel Base</b> 81" (205.7 cm)
<b>Steering</b> .....	Manual, pinion and sector gear system with ergonomically positioned non-adjustable column. Steering wheel has 3 turns lock-to-lock and 17.2 to 1 ratio with a 13.75" (34.93 cm) diameter wheel.		
<b>Turning Clearance Circle</b> .....	Inside rear tire: 87" (221 cm), outside front tire: 257" (653 cm).		
<b>Instrumentation/Dash</b> .....	Hour meter, low oil pressure warning light, accessory power port. Dash has 2 cup holders, radio holder and glove box storage.		
<b>Cargo Bed Size</b> .....	Length: 49" (124 cm), Width: 52" (132 cm), Height: 10" (25 cm), double walled, polyethylene plastic.		
<b>Total Capacity</b> .....	1,250 lbs. (567 kg)	1,650 lbs. (750 kg)	
<b>Cargo Bed Capacity</b> .....	850 lbs. (386 kg)	1,250 lbs. (567 kg)	
<b>Trailer Towing Capacity</b> .....	400 lbs. (182 kg) trailer, 50 lbs. (23 kg) tongue weight with standard hitch. 800 lbs. (363 kg) trailer, 100 lbs. (45 kg) tongue weight with heavy-duty tow hitch.	400 lbs. (182 kg) trailer, 50 lbs. (23 kg) tongue weight with standard hitch. 1200 lbs. (545 kg) trailer, 100 lbs. (45 kg) tongue weight with heavy-duty tow hitch.	
<b>Optional Accessories</b> .....	Canopy, Solid & Folding Windshield, Electric Bed Lift, HD Bumper, Brush Guard, Rahn® Groomer, ROPS, Brake/Tail/Signal Light Kit, Stake Sides, Deluxe Cab, Snow Plow, Deluxe Refreshment Center, Portable Refreshment Center, Slant Board, Heater Kit, HD Trailer Hitch, Rear Lift Kit.		
<b>Warranty</b> .....	Two-year or 1,500 hour limited warranty. Refer to the Operator's Manual for further details.		