TITAN[®] SPECIFICATIONS

MODELS	TITAN [®]				TITAN[®] MX	
	ZX5020	ZX4820	ZX5420	ZX6020	MX4880	MX5480
	74840	74841	74842	74843	74871	74872
Engine	23 hp* KOHLER® Courage PRO	22 hp* Kawasaki [®]	24 hp* Kawasaki	26 hp* Kawasaki	22 hp* Kawasaki	24 hp* Kawasaki
Engine Guard	Standard	Standard	Standard	Standard	Standard	Standard
Frame	Fully Tubular 1.5" x 3"	Fully Tubular 1.5" x 3"				
Fuel Capacity	5 Gallon	5 Gallon				
Deck	50"	48" 10g fabricated with bull-nose bumper	54" 10g fabricated with bull-nose bumper	60" 10g fabricated with bull-nose bumper	48" 10g fabricated with bull-nose bumper	54" 10g fabricated with bull-nose bumper
Deck Depth	4"	4.5"	4.5"	4.5"	4.5"	4.5"
Deck Mount	Standard, no-tools removal	Standard, no-tools removal	Standard, no-tools removal	Heavy duty, no-tools removal	Heavy duty, no-tools removal	Heavy duty, no-tools removal
Spindles	Standard	7.75" dia. / 1" Shaft	7.75" dia. / 1" Shaft			
Discharge Deflector	Polypropylene	Molded Rubber	Molded Rubber	Molded Rubber	Molded Rubber	Molded Rubber
Blade-Tip Speed**	18,000+ ft/min	18,000+ ft/min				
Anti-Scalp Rollers	3 Standard	3 Standard plus Rear Anti-scalp Skids	3 Standard plus Rear Anti-scalp Skids			
Foot Operated HOC	1.5" to 4.5" 13 position	1.5" to 4.5" 13 position				
Transmissions	HG-ZT2800 with charge pumps	HG-ZT3100 with charge pumps, shock valves & heavy duty gears	HG-ZT3100 with charge pumps, shock valves & heavy duty gears			
Ground Speed	7.5 mph	7.5 mph				
Tires (Rear)	20" x 8"	20" x 8"	20" x 10"	20" x 10"	22" x 10"	22" x 10"
Tires (Front)	11" x 4" Smooth	12" x 6" Smooth	12" x 6" Smooth			
Seat	Contoured 18" Extra-Tall	Contoured 18" Extra-Tall	Contoured 18" Extra-Tall	Contoured 18" Extra-Tall	Thickly-padded Toro Premium seat	Thickly-padded Toro Premium seat
Seat Suspension	Adjustable Springs	Adjustable Springs	Adjustable Springs	Adjustable Springs	Full 3-D Isolation	Full 3-D Isolation
Adjustable Armrests	Standard	Standard	Standard	Standard	Padded	Padded
Steering Levers	Dual Comfort Grip™ levers with hydraulic dampers	Dual oversized Comfort Grip™ levers with hydraulic dampers	Dual oversized Comfort Grip levers with hydraulic dampers			
Folding ROPS	Standard	Standard	Standard	Standard	Standard	Standard
Hour Meter	Standard	Standard	Standard	Standard	Standard	Standard
Removable Floor Pan	Standard	Standard	Standard	Standard	Standard	Standard
Width Width w/ Deflector	52.4" 63.1"	53.4" 61.5"	57.7" 67.9"	63" 75"	53.4" 61.5"	57.7" 67.9"
Length	77.3"	77.3"	77.3"	77.3"	77.3"	77.3"
Height ROPS Up Height ROPS Down	73" 46"	73" 46"	73" 46"	73" 46"	74" 47"	74" 47"
Residential and Commercial Warranty <i>†</i>	3-Year Limited/240 Hr	3-Year Limited/240 Hr	3-Year Limited/240 Hr	3-Year Limited/240 Hr	3-Year Limited/400 Hr	3-Year Limited/400 Hr

*The gross horsepower of this engine was laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission and operating requirements, the actual engine horsepower on this class of mower will be significantly lower. ** Blade tip speed is the theoretical maximum speed in feet per minute and is likely to vary. We reserve the right to improve our products and make changes in the specifications, designs and standard equipment without notice and without incurring obligation. †See dealer for warranty details or go to toro.com (US) or toro.ca (Canada).



FLEXIBLE PAYMENT PLANS

Visit toro.com (US), toro.ca (CAN) or talk to your dealer for special finance offers. Offer subject to credit approval. Participating dealers only.





BEST-IN-CLASS WARRANTY

= Enhanced or step-up feature.

Backed by some of the best warranties in the business, you can count on sturdy performance season after season. Ask your dealer about our warranty coverage for specific models.