

The TITAN® combines features from our commercial line of zero turn mowers with the user-friendly features of our residential zero turn mowers creating a pro-inspired, commercial-like machine that's easy to use and comfortable to operate.

## **PRO-INSPIRED FEATURES:**

- ➤ Tubular Commercial-Grade Frame
- ► Heavy Duty Decks Up To 60" Wide
- Premium Transmissions & Twin Cylinder Engines

## **USER-FRIENDLY FEATURES:**

- ► Customizable Comfort
- ► Effortless Maintenance
- Comprehensive Warranties



Count on it.

MODELS	<b>ZX5000</b> 74820	<b>ZX4800</b> 74830	<b>ZX5450</b> 74832	<b>ZX6030</b> 74833	<b>ZX6050</b> 74824
ENGINE					
Engine	22 hp* Briggs & Stratton® Professional Series Twin Cylinder	23 hp* KOHLER® Courage PRO Twin Cylinder	25 hp* KOHLER Courage PRO Twin Cylinder	27 hp* KOHLER Courage PRO Twin Cylinder	26 hp* Kawasaki Twin Cylinder
Engine Guard	Standard	Standard	Standard	Standard	Standard
Fuel Capacity	5 Gallons	5 Gallons	5 Gallons	5 Gallons	5 Gallons
MOWING DECK					
Mowing Deck	50"	48" Fabricated with Bull-Nose Bumper	54" Fabricated with Bull-Nose Bumper	60" Fabricated with Bull-Nose Bumper	60" Fabricated with Bull-Nose Bumper
Deck Spindles	Standard Spindles	1" Dia. Shaft with Oversized Sealed Bearings	1" Dia. Shaft with Oversized Sealed Bearings	1" Dia. Shaft with Oversized Sealed Bearings	1" Dia. Shaft with Oversized Sealed Bearings
Discharge Deflector	Polypropylene	Molded Rubber	Molded Rubber	Molded Rubber	Molded Rubber
Height of Cut	1.5" - 4.5" (1/4" Increments)	1.5" - 4.5" (1/4" Increments)	1.5" - 4.5" (1/4" Increments)	1.5" - 4.5" (1/4" Increments)	1.5" - 4.5" (1/4" Increments)
Blade Tip Speed†	18,000+ fpm	18,000+ fpm	18,000+ fpm	18,000+ fpm	18,000+ fpm
Deck Wash Out Port	2 Standard	2 Standard	2 Standard	2 Standard	2 Standard
TRANSMISSION					
Transmission	Hydro Gear ZT2800 with Charge Pumps	Hydro Gear ZT2800 with Charge Pumps	Hydro Gear ZT2800 with Charge Pumps	Hydro Gear ZT2800 with Charge Pumps	Hydro Gear ZT2800 with Charge Pumps
Ground Speed (F/R)	7.5 / 3.8	7.5 / 3.8	7.5 / 3.8	7.5 / 3.8	7.5 / 3.8
Tires (Rear)	20" x 8.5"	20" x 8.5"	20" x 10"	20" x 10"	20" x 10"
Tires (Front)	11" x 4" Smooth	11" x 4" Smooth	11" x 4" Smooth	11" x 4" Smooth	11" x 4" Smooth
EQUIPMENT					
Seat	Contoured 18" Extra Tall w/Slide & Adjustable Seat Spring Suspension	Contoured 18" Extra Tall w/Slide & Adjustable Seat Spring Suspension	Contoured 18" Extra Tall w/Slide & Adjustable Seat Spring Suspension	Contoured 18" Extra Tall w/Slide & Adjustable Seat Spring Suspension	Contoured 18" Extra Tall w/Slide & Adjustable Seat Spring Suspension
Adjustable Armrests	Standard	Standard	Standard	Standard	Standard
Foot Operated HOC	Standard	Standard	Standard	Standard	Standard
Warranty**	3 Year / 240 Hour & Lifetime Frame Limited Warranty**	3 Year / 240 Hour & Lifetime Frame Limited Warranty**	3 Year / 240 Hour & Lifetime Frame Limited Warranty**	3 Year / 240 Hour & Lifetime Frame Limited Warranty**	3 Year / 240 Hour & Lifetime Fram Limited Warranty**

= Enhanced or Step-up feature







## **HEAVY DUTY DECKS**



#### PREMIUM TRANSMISSIONS & TWIN CYLINDER ENGINES High performing hydrostatic

drive systems and powerful twin cylinder engines provide peak power, smooth operation, and reliable performance.





features such as quick, no washout ports, maintenance free deck spindles and engine oil drain hoses.



#### WARRANTIES

Sturdy performance season after season – backed by one of the best warranties in the business. Ask your dealer about warranty

### **ATTACHMENTS**

- BAGGER (48", 50" & 54")
- HITCH
- LIGHT KIT
- STRIPING KIT
- STEP KIT
- RECYCLER® KIT
- SUNSHADE
- LEAF BAGGING **ENHANCEMENT KIT**
- DELUXE Z COVER
- TRANSPORT SEAT STRAP KIT
- TOW-BEHIND DUMP CART

Ask your dealer for more details.



#### **CUSTOMIZABLE COMFORT** The contoured 18" extra tall seat features an adjustable 4" seat slide, seat spring suspension, and armrests as well as six-way adjustable control levers.



# Effortlessly maintain your mower with easy to use tools deck removal, two deck

FRAME LIMITED WARRANTY details.

<sup>\*</sup>The gross horsepower of this engine was laboratory rated by the engine manufacturer in accordance with SAE J1940. As configured to meet safety, emission, and operating requirements, the actual engine horsepower on this class of mower will be significantly lower. \*\*See dealer or toro.com for warranty details. †Blade tip speed is the theoretical maximum speed in feet per minute and is likely to vary.

<sup>© 2009</sup> The Toro Company, Bloomington, MN 55420. All Rights Reserved. Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features. 490-7990 09/09