

Recycler®	20370	20371	SmartStow™ 20339	20372	20373	20374
Engine**	6.75 ft-lb Gross Torque Kohler® 149cc OHV w/Auto Choke¹	6.75 ft-lb Gross Torque Kohler® 149cc OHV w/Auto Choke¹	7.25 ft-lb Gross Torque Briggs & Stratton® 190cc w/Ready Start²	Toro TXP 159cc OHV w/Auto Choke	Toro TXP 159cc OHV w/Auto Choke	Toro TXP 159cc OHV w/Auto Choke
Starter	Recoil	Recoil	Recoil	Recoil	Recoil	Electric
Self-Propel	Variable Speed Front Wheel Drive	Variable Speed Front Wheel Drive	Variable Speed Front Wheel Drive	Personal Pace® Rear Wheel Drive	Personal Pace Rear Wheel Drive	Personal Pace Rear Wheel Drive
Spin-Stop™ Blade Stop System	N/A	N/A	N/A	N/A	Standard	N/A
PERFORMANCE						
Cutting Width	22"	22"	22"	22"	22"	22"
Deck Material	Steel	Steel	Steel	Steel	Steel	Steel
Height of Cut	1.0" - 4.0"	1.0" - 4.0"	1.0" - 4.0"	1.0" - 4.0"	1.0" - 4.0"	1.0" - 4.0"
Mulch, Rear Bag, Side Discharge	Standard	Standard	Standard	Standard	Standard	Standard
Washout Port	Standard	Standard	Standard	Standard	Standard	Standard
USER FRIENDLY FEATURES						
Handle	1 Piece/Padded	1 Piece/Padded	1 Piece/Padded	1 Piece/Contoured	1 Piece/Contoured	1 Piece/Contoured
Wheel Height	8"	11" Rear, 8" Front	11" Rear, 8" Front	8"	8"	8"
Bag on Demand	N/A	N/A	N/A	Standard	Standard	Standard
Weight	80 lbs.	81 lbs.	83 lbs.	80 lbs.	88 lbs.	86 lbs.
Toro Performance Warranty**	3-Year GTS Full 2-Year Full	3-Year GTS Full 2-Year Full	3-Year GTS Full 2-Year Full	3-Year GTS Full 2-Year Full	3-Year GTS Full 2-Year Full	3-Year GTS Full 2-Year Full

▶ = Enhanced or Step-up feature

ADDITIONAL FEATURES



BAG ON DEMAND
Quickly switch from mulching to bagging with the flip of a lever. 25% better bag fill means you empty the bag less often.



CLOSEEDGE WHEEL DESIGN
Easier to trim and maneuver around landscaped areas.



AUTO CHOKE
No need to choke or prime the engine – just start the mower and go!



WASHOUT PORT
Attach a hose to the mower deck to quickly and easily clean the underside.



ELECTRIC START
No need to pull the recoil cord to start the engine.
(Only on 20334)



SPIN-STOP™
Stops the blade and allows you to briefly step away from the mower, without having to restart the engine.
(Only on 20333)



HIGH WHEEL
The 11" back wheels are great for tackling uneven terrain.
(20371 & 20339)



GUARANTEED-TO-START PROMISE
If it doesn't start in two pulls, we'll fix it for free. Ask your dealer for details.

Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.

490-7382 ©2014 The Toro Company. All rights reserved. ¹The gross torque of this engine was laboratory rated at 2800 RPM per SAE J1940 by the engine manufacturer. ²The gross torque of this engine was laboratory rated at 2600 RPM per SAE J1940 by the engine manufacturer. As configured to meet safety, emission and operating requirements, the actual engine torque on these mowers may be significantly lower. ** See retailer for warranty details.

Recycler®	20370	20371	SmartStow™ 20339	20332	20333	20334
Engine**	6.75 ft-lb Gross Torque Kohler® 149cc OHV w/Auto Choke¹	6.75 ft-lb Gross Torque Kohler 149cc OHV w/Auto Choke¹	7.25 ft-lb Gross Torque Briggs & Stratton® 190cc w/Ready Start®²	7.25 ft-lb Gross Torque Briggs & Stratton® 190cc w/Ready Start²	7.25 ft-lb Gross Torque Briggs & Stratton 190cc w/Ready Start²	7.25 ft-lb Gross Torque Briggs & Stratton 190cc w/Ready Start²
Starter	Recoil	Recoil	Recoil	Recoil	Recoil	Electric
Self-Propel	Variable Speed Front Wheel Drive	Variable Speed Front Wheel Drive	Variable Speed Front Wheel Drive	Personal Pace® Rear Wheel Drive	Personal Pace Rear Wheel Drive	Personal Pace Rear Wheel Drive
Spin-Stop™ Blade Stop System	N/A	N/A	N/A	N/A	Standard	N/A
PERFORMANCE						
Cutting Width	22"	22"	22"	22"	22"	22"
Deck Material	Steel	Steel	Steel	Steel	Steel	Steel
Height of Cut	1.0" - 4.0"	1.0" - 4.0"	1.0" - 4.0"	1.0" - 4.0"	1.0" - 4.0"	1.0" - 4.0"
Mulch, Rear Bag, Side Discharge	Standard	Standard	Standard	Standard	Standard	Standard
Washout Port	Standard	Standard	Standard	Standard	Standard	Standard
USER FRIENDLY FEATURES						
Handle	1 Piece/Padded	1 Piece/Padded	1 Piece/Padded	1 Piece/Contoured	1 Piece/Contoured	1 Piece/Contoured
Wheel Height	8"	11" Rear / 8" Front	11" Rear / 8" Front	8"	8"	8"
Bag on Demand	N/A	N/A	N/A	Standard	Standard	Standard
Weight	80 lbs.	81 lbs.	83 lbs.	80 lbs.	88 lbs.	86 lbs.
Toro Performance Warranty**	3-Year GTS Full 2-Year Full	3-Year GTS Full 2-Year Full	3-Year GTS Full 2-Year Full	3-Year GTS Full 2-Year Full	3-Year GTS Full 2-Year Full	3-Year GTS Full 2-Year Full

= Enhanced or Step-up feature

ADDITIONAL FEATURES



BAG ON DEMAND
Quickly switch from mulching to bagging with the flip of a lever. 25% better bag fill means you empty the bag less often.



CLOSEEDGE WHEEL DESIGN
Easier to trim and maneuver around landscaped areas.



AUTO CHOKE
No need to choke or prime the engine – just start the mower and go!



WASHOUT PORT
Attach a hose to the mower deck to quickly and easily clean the underside.



ELECTRIC START
No need to pull the recoil cord to start the engine.
(Only on 20334)



SPIN-STOP™
Stops the blade and allows you to briefly step away from the mower, without having to restart the engine.
(Only on 20333)



HIGH WHEEL
The 11" back wheels are great for tackling uneven terrain.
(20371 & 20339)



GUARANTEED-TO-START PROMISE
If it doesn't start in two pulls, we'll fix it for free. Ask your dealer for details.

Specifications subject to change without notice and without incurring obligation. Products depicted on this sell sheet are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.

490-7383 ©2014 The Toro Company. All rights reserved. ¹The gross torque of this engine was laboratory rated at 2800 RPM per SAE J1940 by the engine manufacturer. ²The gross torque of this engine was laboratory rated at 2600 RPM per SAE J1940 by the engine manufacturer. As configured to meet safety, emission and operating requirements, the actual engine torque on these mowers may be significantly lower. ** See retailer for warranty details.