

Multi Pro® 5700-D





Multi Pro® 5700-D

- 300 gallon (1136 liter) tank
- Pro Control™ Sprayer System
- 18.5' (5.6 m) boom width
- 35.5 hp (26.5 kW) Kubota[®] water-cooled diesel engine

Precision & Productivity.

The Toro® Multi Pro 5700-D stands out for its ability to handle the biggest jobs. Attribute its productivity to a new 35.5 hp (26.5 kW) Kubota diesel engine and a 300-gallon (1136 liter) tank. A large wingspan and a dual diaphragm pump deliver spray consistency you won't find anywhere else. Plus,

you can add the Toro Pro Control Sprayer System, which calibrates speed and terrain changes to ensure a precise application rate.



Count on Durability

Toro builds a better boom.

Trees, benches and other obstacles are no match for the rugged new boom design on the Multi Pro 5700-D. A triangular frame protects the spray nozzles from direct impact. Combined with the breakaway boom design, it's the ultimate defense against unexpected impact.



Greener grass faster.

Everything about the new Multi Pro 5700-D is geared toward productivity, starting with a three-section boom that spans 18.5' (5.6 m), giving you one of the widest coverage spans of any dedicated sprayer. In addition, the fan pattern of each nozzle provides 100% overlap to ensure maximum turf coverage. By producing larger droplets, the spray lands directly on the turf, reducing drift. The powerful 35.5 hp (26.5 kW) Kubota® diesel engine is up to any task, maintaining a consistent application rate over even the most difficult terrain.



Fingertip boom switches and a foot pedal on/off switch are ideal for driving and operating the boom simultaneously.



As added protection on windy days, the available enclosed boom prevents spray particles from drifting off course.

A breakaway boom design prevents damage, allowing you to spray around obstacles with confidence.





Quality control.

The ultimate in precision spray control and efficiency is at your fingertips with the optional Toro Pro Control™ Sprayer System. This system automatically calibrates and maintains an even rate of spray while changing speeds or traveling over varied terrain, thanks to an advanced software platform that responds instantly to changes. Pro Control allows for independent control of each boom section and automatically shuts off spray when the vehicle stops. Program multiple application rates on the user-friendly control panel, or press the manual override button for manual spot spraying.



With optional Pro Control, your Multi Pro 5700-D is the most precise sprayer on the market, saving you time and money.

Pump it up.



Precision spraying demands a quality pump. That's why Toro gave the Multi Pro® 5700-D a dual diaphragm pump capable of pumping up to 30 gallons per minute (114 liters/min). It can also produce up to 220 psi of pressure for hand-spray applications. The entire sprayer is exceptionally functional thanks to user-friendly

features like the top-suction system that places the strainer at the top of the tank, along with the drain control, for easy access. A deep strainer basket allows water-soluble bags and powders to dissolve easily without clogging the pump.



Operator conveniences include a large fresh water tank and a compartment for safety gear.



Accessories

The Toro Multi Pro 5700-D can be upgraded with several attachments that increase its versatility.

Electric hose reel









Also Available:

- Single-nozzle kit
- Enclosed walk boom
- Pro Control[™]
- Covered boom
- Sonic Boom[™] kit

Specifications for Multi Pro® 5700-D

Model: Kubota® 4-cylinder

Rating: 35.5 hp (26.5 kW) @ 3000 rpm Displacement: 91 cu. in. (1491 cc)

Traction Unit

Fuel capacity: 10.6 gallon (40 liter), diesel

Brakes: Multi-disc, hydrostatic braking through traction drive Suspension: Front independent leaf springs w/dual shock absorbers

Tires

Front: 23 x 10.5-12, 4-ply rating, turf tread Rear: 26.5 x 14-12, 4-ply rating, turf tread

Ground Speed

Forward: 0-10 mph (0-16 km/h) Reverse: 0-4 mph (0-6.4 km/h)

Steering: Full hydraulic power, 51° steering angle

Controls: Master boom on/off switch, pressure increase/decrease, hydraulic spray pump, agitator, individual boom on/off switches, boom lift, traction pedal lock, sprayer pressure gauge

Weight & Dimensions (w/spray system in storage cradle)

Empty vehicle: 2,700 lbs. (1,225 kg) Full w/operator: 5,845 lbs. (2,651 kg) MGVW: 6,525 lbs. (2,960 kg) Wheelbase: 78" (198 cm)

Length: 174" (442 cm)

Width w/spray system: 74.75" (189 cm)

Height: 91" (231 cm)

Sprayer Specifications

Solution tank: High density, impact resistant polyethylene

Capacity: 300 gallon (1,136 liter)

Fillwell: 16" (41 cm)

Spray pump: Dual diaphragm, 30 gpm (114 liter/min) output, capacity

range up to 220 psi (1500 kpa) Agitator: Three jet agitators

Options: Pro Control™ system, Pro Foam marking system,

electric hose reel, spray gun kit, operator enclosure, ROPS, speedometer

kit, single nozzle kit

Open Boom (standard)

Boom assembly: 3-section, 18.5' (5.6 m) working width, electric boom

lift standard, Sonic Boom™ for added boom control

Spray nozzles: Drift reduction, quick-disconnect with diaphragm check

valves, turret style

Enclosed Boom (optional)

Boom assembly: 3 section, 18.5' (5.6 m) working width, electric boom

Spray nozzles: 11 nozzles, 20" (51 cm) spacing, 110° extended range flat fan spray tips, quick-disconnect with diaphragm check valves

Wheels: 15 x 6.00-6, Turf Rib

Enclosed Walking Boom (optional)

Boom assembly: 3 section, 7' (2.0 m) working width

Spray nozzles: 4 nozzles, 20" (51 cm) spacing, 110° extended range flat

fan spray tips, quick-disconnect with diaphragm check valves

Wheels: 10 x 3.50/5-1.75

Certification: ANSI B71.4-1999, CE certified

Warranty: Two-year limited

TORO® PROFESSIONAL SERVICES

Toro Financing A full service offering for all your equipment and irrigation purchases. Flexible financing options can be tailored to meet your operational needs.

Toro Protection Plus Extended Protection Plan Protect your budget and your equipment investment. Plans are available for both new and used equipment, and you can choose from various terms to fit your financing terms.

Toro Genuine Parts Keep the productivity and performance of your equipment at its peak. Learn about Performance Parts pricing and MVP kits. Find replacement parts online at Toro.com/ partsviewer.

Toro Training Toro Factory Service Schools are available. Explore the training and customer care areas of Toro.com and ToroNSN.com for readily available education and training materials.

Toro Controller Repair Provides irrigation controller boards ready for immediate board exchange to assure that downtime is minimal and your turf stays protected. Toro is the choice for reliability.

Toro NSN® An industry-first support network that provides reliable, around-the-clock irrigation central control system troubleshooting and operation assistance. Call 1-800-ASK-TORO.

Products depicted in this brochure are for demonstration purposes only. Actual products offered for sale may vary. ©2005 The Toro Company, 8111 Lyndale Ave. S., Bloomington, MN 55420-1196 Part No. 05-080-T. Printed in U.S.A.

