Material Safety Data Sheet



The Toro Company 8111 Lyndale Ave S Bloomington, MN 55420

Revision Date: 07/25/09

Issue Date: 08/08/09

Product Identification

Product Name:	Toro Xtreme Colors Paint	Parts Number:
Product type:	paint	42025, 42026, 42027, 42028, 42029
MSDS #		
Emergency	Chemtrec : 1-800-424-9300	
Contact:		
Contact Number:	1-952-888-8801	

Chemical Components

Chemical	CAS #	%	ACGIH TLV	OSHA PEL	Other
Vinyl -Acrylic water-based line marking paint.					

Physical and Chemical Properties

Characteristics		Physical Properties		Hazards Description	Physical Dangers
Physical State	liquid	Vapor pressure			Toro Extreme is stable under normal conditions of
Color	Red, Yellow, Green, Blue	pH Boiling point/range:	7.0 to 8.0 Approx. 100 _o C		use
Odor	and Black slight	Melting point/range:			
HMIS Ratir Health:	ng	Specific gravity Vapor density	1.5 to 1.7		
Flammabil	ity:	Evaporation rate			
Physical Hazard:		Solubility in water VOC content: Flash Point	Fully miscible		

Health Hazards

Major Rout Exposure:		Ingredients Considered Hazardous to Health	Potential Health Effects:
Inhalation		none	Inhalation.
Skin	Х		Skin contact: Prolonged or repeated contact may
Ingestion		7	cause irritation of the skin.
Eye	Х		Eye contact:. Direct contact with this material may
			cause irritation.
			Ingestion:

First Aid Measures	Personal Protection
EYE CONTACT: Flush eyes immediately with copious	EXPOSURE CONTROLS: Local exhaust ventilation may be
amounts of water. Continue to flush for at least 10	required in circumstances where the product is sprayed,
minutes.	heated or dried in confined spaces.
Seek medical advice if irritation persists.	PERSONAL PROTECTION:
SKIN CONTACT: Remove contaminated clothing. Wash	Respiratory: If sprayed in confined spaces e.g. indoors,
with soap and water before fluid dries.	masks may be required.
INGESTION: Drink plenty of water. Do not induce	Hand: Gloves, if risk of skin contact.
vomiting.	Eye: Goggles, if risk of splashing.
Seek medical advice	Skin: Standard industrial overalls if risk of splashing.

Fire and Explosion Hazards

-		
Extinguishing Media	Special Fire Fighting Procedures	Unusual Fire and Explosion
		Hazards
Water, foam, carbon dioxide or dry powder extinguishers are all suitable		Aqueous dispersions will not burn. Dried films are combustible. Material will spatter above 100 ₀ C. FLASH POINT: Non-combustible AUTO-IGNITION TEMPERATURE: Not Applicable

Handling and Storage

Accidental Release /Spill Measures to Take	Precautions for Storage	Handling
Spillage should not be washed into any drain	Keep from freezing; product may	Handle in accordance
unless it leads to a suitable effluent treatment	coagulate.	with good industrial safety
process. Residues and spillage should be soaked	Store in sealed containers between	and hygiene practices.
up with an inert absorbent (e.g. sand, earth) for	5₀C and 25₀C.	
disposal.		

Disposal/Transportation

Disposal Method	Transportation
Toro Extreme Colour is not classified as hazardous waste. This product can be coagulated and separated from the aqueous phase for landfill or incineration. The residual liquid should not be discharged without prior consent. Existing National and Local Regulations must always be complied with.	Toro Extreme Colour is not classified as hazardous for transportation.

Regulations

Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP): Therapeutic Goods Act (1989) No Poisons Schedule number allocated EEC Hazard Classification: None

Toxicology Information

Acute oral toxicity: LD₅₀ (RAT) > 2000 mg/kg Method: EEC 84/449, B.1 Irritant effect on skin: Slight (Rabbit) Method: EEC 84/449, B4 Irritant effect on skin: Slight (Rabbit) Method: EEC 84/449, B5 The product is therefore considered to be of low acute oral toxicity to mammals. Frequent contact may lead to skin and eye irritation, especially if the product is allowed to dry out. Long term experience of handling of this product under Industrial conditions indicates the absence of any chronic or acute effects. This product is considered to be harmless to health if used in the correct manner. The toxicological data given are determined by analogy.

Ecological Information

Chemical Oxygen Demand (C.O.D): Chemical Oxygen Demand (C.O.D):

(Wash-down, i.e. low concentration @ <500mg/l). **Toro Extreme Colour** paint is totally miscible with water and at low concentrations, exhibits low toxicity to fish.

According to experience, this product has no harmful effect to the environment if used in the correct manner.

Toro Australia Pty Ltd classify this product as non-hazardous or toxic under normal conditions of use. The information provided in this Safety Data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be carried out and should not be construed as a guarantee of specific properties.